



MADE FOR LIFE UNDER THE SUN



Before It Becomes a Problem

Inspecting, maintaining and planning the life of outdoor structures

How outdoor structures change, what to look for,
and how to decide what to do next.

INSPECTION · MAINTENANCE · MONITORING · REFURBISHMENT · LIFECYCLE

Performance Beyond Installation.

CONTENTS

What is in this guide

Twenty-five short sections in five parts. Read it once to change how you think about the asset; then use Part Two on site and Part Three to build the routine.

PART ONE — THE ASSET AFTER INSTALLATION

- 01** What happens after everyone stops thinking about it
- 02** Between new and broken
- 03** Six different questions
- 04** The lifecycle model

PART TWO — UNDERSTANDING CONDITION

- 05** Why outdoor structures change here
- 06** Age is not condition
- 07** What to look for: the covering
- 08** What to look for: structure, connections and cables
- 09** What to look for: foundations, interfaces and drainage
- 10** Early warning signs, and what to do about them

PART THREE — BUILDING THE ROUTINE

- 11** Baseline condition: the record you only get once
- 12** Planning inspection, and setting your own intervals
- 13** Monitoring: watching change over time
- 14** Preventive and corrective maintenance
- 15** After the storm: event-based inspection
- 16** Condition and consequence: setting priorities

PART FOUR — DECISIONS AS THE ASSET AGES

- 17** Repair: fixing the problem, or the cause?
- 18** Refurbishment: extending useful life
- 19** When replacement is the better decision
- 20** Responsible lifecycle decisions

PART FIVE — RUNNING IT AS A SYSTEM

- 21** Documentation: preserving the memory of the asset
- 22** Building an outdoor asset register
- 23** Lifecycle budgeting



ZIL

SHADES

MADE FOR LIFE UNDER THE SUN

BEFORE IT BECOMES A PROBLEM

24 Common mistakes to avoid

25 The lifecycle checklist

HOW TO USE THIS GUIDE

Two levels, and three kinds of box

This guide serves a villa owner who wants to know whether the sag in their car park shade matters, and a facility team building an inspection regime across a portfolio. The running text is written for both. Three recurring boxes carry the rest.

BOX	WHO IT IS FOR	WHAT IT DOES
What to look for	Everyone	A short observation list you can walk a site with. No tools, no training, no climbing.
When to seek assessment	Everyone	The conditions that should stop you and bring in a qualified professional. If you read nothing else, read these.
For facility and asset teams	Facility, property and asset managers	The structured version: registers, intervals, prioritisation, records and budgeting.

TWO LINES THIS GUIDE WILL NOT CROSS

It states no inspection frequencies, maintenance intervals, material lifespans or failure thresholds. Those depend on the asset, its exposure, its consequence of failure and its known condition — and a number invented for a guide would be worse than none. Section 12 shows you how to derive your own instead.

Observation is not intervention. Anyone can look at a structure and record what they see. Adjusting tension, tightening structural connections, or altering a member is work for people qualified to do it, following the requirements the structure was designed to.

Where this guide sits

GUIDE	THE QUESTION IT ANSWERS
Before You Buy Shade	Should I add an outdoor structure at all, and what should I ask before I sign?



GUIDE	THE QUESTION IT ANSWERS
Before You Issue the RFQ	How do I specify, procure, evaluate and hand over the asset?
Before You Approve the Material	What is it made of, and why do those material decisions matter?
Before It Becomes a Problem — this guide	What happens after installation, how should the asset be understood across its life, and how should decisions be made as it changes?



The asset after installation

An outdoor structure is not either new or broken.
Almost all of its life is spent somewhere in between.

-
- 01 What happens after everyone stops thinking about it
 - 02 Between new and broken
 - 03 Six different questions
 - 04 The lifecycle model

01 What happens after everyone stops thinking about it

An outdoor structure gets a great deal of attention for a few months. It is discussed, designed, quoted, argued over, approved, built and handed over. Then the attention stops.

Often it does not resume until something demands it. The fabric sags. Rust appears. Water ponds after a downpour. A component works loose. A storm does something visible. A tenant complains, a car is damaged, a bay is closed off with cones, and somebody makes an urgent phone call.

That cycle — **ignore, emergency, repair, ignore again** — is the default way most outdoor assets are managed in this region. It is not the result of negligence. It is the result of nobody ever deciding who was watching, or what they were watching for.

It is also the expensive way. Work done in an emergency costs more than the same work planned. Areas closed without warning disrupt more than areas closed by appointment. And a defect found late is usually a bigger defect than the same one found early.

WHAT THIS GUIDE CLAIMS, AND WHAT IT DOES NOT

It does not claim that inspection prevents all problems. Some things break, and weather does what it does.

It claims something more modest and more useful: **early understanding improves the quality and the timing of your decisions.** You get to choose when to act, what to spend, and how much disruption to accept — instead of finding out on the worst possible morning.

02 Between new and broken

Most people carry a two-state model of outdoor structures in their heads. The structure is either fine, or it is a problem. There is nothing in between, so nothing needs doing until something goes wrong.

Almost the entire life of an asset is spent in between.

A structure may be new; stable; ageing normally; showing minor deterioration; due for maintenance; under observation because something is changing; repairable; a candidate

for refurbishment; approaching the end of its useful life; or ready to be decommissioned. Those are ten different situations calling for ten different responses, and only two of them are the ones most owners recognise.

Lifecycle management is simply the discipline of knowing **which of those states your asset is in today**, and what the appropriate next decision is. That is the whole idea. Everything else in this guide is method.

THE PRINCIPLE

The absence of a visible failure is not the same as the absence of deterioration. An asset that looks acceptable may be perfectly healthy, or may be a year into a process nobody has noticed. The difference between those two situations is not visible from a distance — which is exactly why somebody has to look properly.

03 Six different questions

Six words get used almost interchangeably in this field, and the confusion causes real problems — a client who asks for maintenance and receives an inspection, or who expects a refurbishment and is quoted a repair. They are six different activities answering six different questions.


ACTIVITY	THE QUESTION IT ASKS	WHAT IT PRODUCES
Inspection	What is the condition of this asset?	A record: observations, photographs, comparison with what was recorded before, and a list of findings.
Maintenance	What should be done to keep it performing as intended?	Work carried out — cleaning, clearing drainage, minor corrective action, planned attention.
Monitoring	Is this particular condition changing over time?	A tracked observation with a review date and a defined trigger for further action.
Repair	Can this localised problem be corrected?	A specific defect put right.

ACTIVITY	THE QUESTION IT ASKS	WHAT IT PRODUCES
Refurbishment	Can significant parts be renewed to extend useful life?	A planned intervention — fabric replacement, recoating, component renewal, upgrade.
Replacement	Has continued intervention stopped making sense?	A new asset, and the responsible removal of the old one.

Two practical consequences. First, **an inspection is not maintenance**. Knowing the condition of something changes nothing on its own; it is what makes the next decision a good one. Second, **repair and refurbishment are different commitments** — one corrects a defect, the other renews a significant part of the asset — and asking for a price without naming which you mean is how quotations become non-comparable.

04 The lifecycle model

The whole of this guide fits into one picture: a line that happens once, a loop that repeats for the life of the asset, and an exit that happens once.



The outdoor asset lifecycle. Most of an asset's life is spent going round the loop.

Three things in that picture are worth saying out loud.

- **The baseline is the hinge.** It is where the line becomes the loop, and it is the only stage you cannot go back and do later. Section 11 is about why.
- **“Decide” is a step, not a formality.** Observing a defect and acting on it are separated by a judgement: does this matter, how much, and what is the right response? Skipping that judgement is what produces years of patching the same corner.
- **The exit is reached from condition, not from a date.** An asset is replaced because continued intervention no longer makes sense — not because it has had a particular number of birthdays.

The loop is not tidy in practice. An asset may be inspected, monitored for a season, maintained, inspected again, repaired, and monitored once more, many times over. That is not the model failing. That is the model working.



Understanding condition

The calendar age of an asset is useful information, but age alone does not describe condition.

-
- 05 Why outdoor structures change here
 - 06 Age is not condition
 - 07 What to look for: the covering
 - 08 What to look for: structure and connections
 - 09 What to look for: foundations and drainage
 - 10 Early warning signs

05 Why outdoor structures change here

Nothing in this section is a warning. It is simply the operating environment, and it explains why an outdoor asset in this region needs more attention than the same asset in a mild climate.

- **Ultraviolet light** works on fabrics, coatings and plastics continuously, through every month of the year.
- **Heat and daily thermal cycling** expand and contract every component, working at fixings and at any joint between two materials that move by different amounts.
- **Dust** settles in every joint, fills drainage outlets, holds moisture against metal, and abrades fabric wherever something moves against something else.
- **Humidity and coastal salt** drive corrosion, and change what an adequate protection system looks like from one site to another a few kilometres away.
- **Wind** fatigues and loosens over time. The damage is usually cumulative rather than dramatic.
- **Rain** arrives rarely and then tests every drainage assumption at once.

Two of these deserve emphasis because they are the ones that catch owners out.

Dust is not a cleanliness issue. It is the mechanism behind blocked outlets, abrasion at fabric contact points, and moisture retained against steel long after the air has dried. Clearing it is genuine maintenance.

Rain being rare is exactly why drainage gets forgotten. A structure can look entirely acceptable for eight or ten months. Then a real downpour arrives, and the ponding nobody predicted, the outlet nobody cleared and the detail that channels water onto a walkway all appear on the same afternoon.

06 Age is not condition

The most common question asked about an ageing structure is how old it is. It is useful information and a poor answer.

Two structures installed in the same month can be in entirely different condition ten years later — because one is inland and one is coastal, because one was properly detailed and

one was not, because one has been cleaned and re-tensioned and one has been forgotten, because one was hit by a delivery truck in year three and repaired badly.

THE PRINCIPLE

The calendar age of an asset is useful information, but age alone does not describe condition. A ten-year-old structure that has been maintained may be in better condition than a four-year-old one that has not.

This cuts both ways. Age is not a reason to replace something that is performing. It is also not a reason to assume something young is fine.

What actually determines condition is the combination of material and design; the exposure the asset actually sits in; the quality of the original installation; how it has been used, loaded and modified; whether it has been damaged and how that damage was dealt with; and whether anyone has been maintaining it. Age is one input among seven.

FOR FACILITY AND ASSET TEAMS

This has a direct budgeting consequence. Replacement forecasting built on installation dates alone will over-replace healthy assets and under-anticipate the ones deteriorating fastest. **Condition-based forecasting requires condition data**, which requires inspection, which is the argument for having a regime at all.

07 What to look for: the covering

The membrane or fabric is the part everybody sees, and usually the first place a problem becomes visible. Much of what changes here is normal ageing rather than a defect – the skill is telling the two apart, and the reliable way to do that is comparison over time rather than judgement in the moment.

**ZIL**

SHADES

MADE FOR LIFE UNDER THE SUN

BEFORE IT BECOMES A PROBLEM

WHAT TO LOOK FOR

Shape and tension — sagging that was not there before, or has increased. Areas that look slack while the rest is taut. Wrinkles that stay in the same place.

Water — ponding after rain, or a stain pattern showing where water has been sitting. Note that a pond deepens under its own weight, so a small one is not a small problem.

Damage — tears, punctures, abrasion, frayed edges, and anywhere the fabric rubs against a bracket, cable or edge.

Edges and corners — the highest-stressed parts of any membrane, and where problems almost always start. Look at the corners first, not last.

Seams — any sign of separation, lifting or opening along a welded line.

Surface — discolouration, dirt accumulation and staining. Usually cosmetic; useful mainly as a record of change.

Previous repairs — patches, tapes and fixes. Note them, and note whether the same location has been repaired more than once.

Interpret in context. Slight colour change over years is expected. New slackness in one bay of a structure that was uniform last year is not — it is a change, and change is the thing worth reporting.

WHEN TO SEEK ASSESSMENT

A tear of any size in a structural membrane · ponding that is present after every rainfall or is deepening · slackness that returns after re-tensioning · seam separation · repeated damage in the same location · any change in the overall shape of the structure.

08 What to look for: structure, connections and cables

The steel, the connections and the cables are where consequence lives. Most of what matters here is visible from the ground with nothing more than attention and, if the structure is tall, a zoom lens.



WHAT TO LOOK FOR

Corrosion — rust staining, blistered or flaking coating, and particularly any rust at base plates, at bolted joints, at welds, and around anything drilled on site. Note where it is, not just that it exists.

Coating condition — chalking, fading, chipping, and damage from impact, cleaning or nearby work.

Water traps — anywhere water or wet dust sits against steel: flat surfaces, unsealed hollow sections, the top of a base plate.

Deformation — a member that is bent, twisted, or no longer in line with its neighbours. Compare against an old photograph if you have one.

Impact damage — vehicle strikes at column bases are common, and are frequently unreported.

Connections — missing bolts, nuts or washers; visible gaps; rust weeping from a joint; bolts that appear to have moved.

Cables and fittings — corrosion, broken or protruding strands, damaged or distorted fittings, and any change in cable alignment or apparent slackness.

Modifications — signage, lighting, cladding, cameras or anything else added since installation. Note it. Somebody added load to a structure that was designed without it.

On rust, one distinction is worth carrying: **surface rust and section loss are not the same thing.** A light bloom on a scratch is a coating problem. Rust flaking away in layers, or metal that has visibly lost thickness, is a structural question. From the ground you often cannot tell which you are looking at — and that is a legitimate reason to ask for an assessment rather than a reason to panic.

WHEN TO SEEK ASSESSMENT

Any rust that appears to involve loss of material rather than surface staining · corrosion at a base plate, a cable termination or a main connection · a missing structural bolt · a member that is bent or out of line · a bolt that repeatedly works loose in the same place · any visible crack in steel or in a weld · a cable with broken strands · any modification made without assessment.



OBSERVATION IS NOT INTERVENTION

Everything in this section is looking and recording. **Do not tighten, adjust, re-tension or straighten anything.** A bolt that keeps loosening is telling you something is moving, and tightening it removes the evidence without addressing the cause. Structural adjustment and re-tensioning are work for people qualified to carry it out, following the requirements the structure was designed to.

09 What to look for: foundations, interfaces and drainage

The parts nobody photographs, and where a surprising share of expensive problems begin.

WHAT TO LOOK FOR

Around the bases — cracking in the surrounding surface, settlement, a column that looks out of plumb, or a gap opening where the base meets the paving.

Water at the bases — standing water, damp patches that never dry, irrigation spraying onto steel, or drainage that discharges next to a foundation.

Interfaces — where the structure meets a building: staining, damaged sealant, damp on the inside face, or damage to render or waterproofing around fixings.

Drainage outlets and gutters — dust, debris, plant growth, or an outlet that has clearly not been cleared in a long time.

Where water actually goes — follow it after rain if you can. It is the single most informative ten minutes available to anyone responsible for one of these structures.

Ground changes — new landscaping, new paving levels, excavation nearby, or anything that has altered how water moves across the area.

Visible cracking in a surface near a column does not automatically mean the foundation has failed. Concrete cracks for many reasons, most of them harmless. What matters is the location, the pattern, and whether it is changing — which is a question for someone competent to answer, and a good example of a condition worth monitoring rather than either ignoring or panicking about.

WHEN TO SEEK ASSESSMENT

A column that appears out of plumb or has moved · cracking that is widening, or is at a base or a fixing point · persistent standing water at a foundation · water penetrating a building at a fixing point · drainage that has been blocked long enough for water to have found another route.

FOR FACILITY AND ASSET TEAMS

Drainage is the cheapest item on any maintenance schedule and the one most often left off it. **Clearing outlets before the rainy season is a scheduled task, not a reactive one**, and it is worth naming explicitly in a maintenance scope rather than assuming it sits inside “cleaning”.

10 Early warning signs, and what to do about them

Some observations deserve to move faster than the next scheduled inspection. None of them proves that failure is imminent; each is a reason to find out whether the condition is significant.

SIGN	WHY IT MATTERS
New or increasing sag	Something has changed — tension, a fixing, a support, or the fabric itself.
Water ponding	Self-worsening: the weight of the water deepens the pond, which collects more water.
A tear or puncture in a membrane	In a structural membrane this is a structural item, whatever its size.
Unusual movement or noise in wind	Slack fabric, a loose component, or a connection that is working.
Loose or missing components	Load is transferring through fewer elements than the design intended.
Corrosion in an unexpected place	Usually means water is going somewhere nobody expected it to go.

SIGN	WHY IT MATTERS
Repeated leakage in the same spot	A detail problem, not a sealing problem. Sealing it again will not fix it.
Cracking or movement near a support	The interface between structure and ground is the least forgiving part of the asset.
Damage after a storm	Events reveal weaknesses rather than creating them. See section 15.
The same repair, more than twice	The repair is treating a symptom. The cause has never been found.
Impact damage	Frequently unreported, and frequently at a column base.

A four-step response that works for any of them

- **Observe.** Record what you can see: date, location, photographs from a repeatable position, and a plain description.
- **Compare.** Put it beside the baseline record or the last inspection. Has this always looked like this, or has it changed? This one question resolves a large share of concerns.
- **Assess.** Decide whether it needs professional assessment. The boxes throughout Part Two tell you where that line sits.
- **Act.** Repair, maintain, monitor, restrict use, or record and carry on — as a decision, with a date attached to it.

THE MOST USEFUL HABIT IN THIS GUIDE

Photograph each structure from the same two or three positions at every inspection, and keep the photographs somewhere findable. It costs ten minutes. It converts every future argument about whether something has changed into a matter of fact.



Building the routine

The objective of inspection is not to find fault.
It is to understand condition.

-
- 11** Baseline condition
 - 12** Planning inspection
 - 13** Monitoring change over time
 - 14** Preventive and corrective maintenance
 - 15** After the storm
 - 16** Condition and consequence

11 Baseline condition: the record you only get once

When an asset enters service, somebody should record what it looks like and what it is. That record is the baseline, and it is the reference every future observation will be compared against.

Without it, a new facility manager in year six is left with an unanswerable question: **has this always looked like this, or has something changed?** With no way to answer it, every observation becomes either an alarm or a shrug — and both are expensive.

FOR FACILITY AND ASSET TEAMS

A baseline is worth establishing at four moments: **at handover of a new asset; when you take over an existing one** you did not procure; **when a property changes hands**; and **immediately after any refurbishment**, because the asset that comes out is not the asset that went in.

It need not be elaborate. Asset identification and location; installation date where known; photographs from repeatable positions; the drawings and material information handed over; the warranty position; any conditions already present on day one; and the contact details of whoever built it.

That last item — conditions already present on day one — is the one people leave out and later wish they had not. A mark, a slight unevenness, a stain that was there at handover is not a deterioration. Without a record, it becomes one.

Baselines also decide warranty conversations. A claim rests on showing that a condition arose after installation and was not the result of neglect. A baseline record and a maintenance history do that. Their absence rarely helps the claimant.

12 Planning inspection, and setting your own intervals

The question everybody asks is how often. This guide will not answer it with a number, because the honest answer depends on your asset — and a frequency invented for a general guide would be either wasteful or unsafe depending on who applied it.

What it will do is show you how to derive your own, from four inputs you already have.

INPUT	WHAT TO CONSIDER	WHICH WAY IT PUSHES
Consequence of failure	What is beneath and around the structure: people, public access, vehicles, critical operations.	Higher consequence → shorter interval, and a more thorough inspection.
Exposure	Coastal air, high dust, heavy wind exposure, structures over irrigation or standing water.	Harsher exposure → shorter interval.
Age and condition history	How the asset has behaved so far, and whether anything is already being tracked.	Known deterioration → shorter interval, or formal monitoring.
Access and disruption	How hard and how disruptive inspection is.	Difficult access → fewer, better-planned inspections, and more value from doing each one properly.

Set the interval from those four, write down the reasoning, and review it when the inputs change. A documented interval with a stated basis is defensible; an undocumented one is a habit.

FOR FACILITY AND ASSET TEAMS

Three further things make an inspection regime work in practice. **Define what an inspection covers** — a walk-round looking at the covering and the bases is a different activity from a close inspection of connections and terminations, and both have their place. **Define who does what:** routine observation can be done by site staff with the boxes in Part Two; assessment of anything structural cannot. And **define what happens to the findings** — an inspection that produces a report nobody actions has consumed budget and changed nothing.

Two additional triggers belong in any regime alongside the routine interval: **event-based inspection** after storms and impacts (section 15), and **change-based inspection** whenever something is added to, fixed to, or built next to the structure.

13 Monitoring: watching change over time

Monitoring is not inspecting more often. It is deliberately tracking one known condition to find out whether it is changing — because in many cases the significance of a defect is not in its size but in its direction.

A crack that has been the same for four years and a crack that has grown since March are different situations, and they look identical in a photograph taken today.

Monitoring is the right response when a condition is known but its significance depends on whether it moves; when a repair is planned but cannot be done immediately; when an asset is approaching a refurbishment decision; or when something has been repaired and you want to know whether the repair is holding.

FOR FACILITY AND ASSET TEAMS

A monitoring entry that works has five parts, and it is worth insisting on all five: **what is being observed** (specific location, not “the canopy”); **how it is recorded** (photograph from a fixed position, a measurement, a note); **how often it is reviewed**; **who reviews it**; and **what change would trigger further action**.

The last one is what separates monitoring from procrastination. Without a defined trigger, an item stays on a watch-list indefinitely and nobody ever decides anything. The trigger should be set by someone competent to set it for that asset.

A CAUTION

Monitoring is appropriate for conditions that have been assessed and judged suitable for observation. It is not a way of deferring a decision about something that has never been assessed at all. If nobody has looked at it properly, the answer is not monitoring — it is assessment.

14 Preventive and corrective maintenance

Two kinds of work, and it is worth naming which is which, because they are budgeted differently and they succeed differently.

	PREVENTIVE	CORRECTIVE
Purpose	Reduce avoidable deterioration and find conditions early.	Put right a defect that has been identified.
Typical work	Cleaning; clearing drainage outlets; checking accessible fixings; touching up minor coating damage; scheduled inspection.	Repairing a tear; renewing a failed fitting; recoating a corroded area; correcting a drainage fault.
When it happens	On a schedule, whether or not anything is wrong.	In response to a finding.
Budget behaviour	Predictable, modest, easy to plan.	Variable, and expensive when it becomes urgent.

Preventive maintenance does not eliminate failures, and a guide that promised otherwise would be lying. What it does is remove the avoidable ones — the blocked outlet, the dust-packed joint, the small coating chip that becomes a rust patch — and surface the rest while they are still small and still cheap.

The most valuable preventive work on these structures is also the least technical: keeping drainage clear, keeping dust out of joints and moving parts, washing exposed metal in coastal locations, and looking properly at whatever interval you have set.

15 After the storm: event-based inspection

Some inspections should not wait for the schedule. After a significant event, the asset has been tested in a way that no routine visit reproduces.

Events worth an additional look include severe wind; heavy rainfall; any storm; vehicle or equipment impact; fire or heat exposure nearby; any modification to the structure; and construction, excavation or landscaping work close to the supports or foundations.

WHAT AN EVENT ACTUALLY DOES

A storm rarely creates a defect out of nothing. It **reveals** the ones that were already present – the fixing that was already loose, the panel that was already slack, the corroded plate, the modification nobody assessed.

Which means a post-event inspection is not only about damage. It is one of the most informative condition assessments you will ever get, because the structure has just been loaded in a way you cannot arrange deliberately.

A structure can also look entirely acceptable immediately after an event and still warrant further observation. Movement that has occurred, fixings that have worked, or a membrane that has been overstressed do not always announce themselves the next morning. Where an event was significant, it is reasonable to look again a few weeks later rather than assuming the first look settled it.

WHEN TO SEEK ASSESSMENT

Any visible damage after an event · any change in shape or tension · standing water where there was none before · movement at a base or fixing · a structure that behaved noticeably differently during the event, even if nothing is visibly wrong now.

16 Condition and consequence: setting priorities

An inspection of a portfolio produces a list, and the list is always longer than the budget. What gets done first should not be decided by whichever item is easiest to picture.

Two things decide priority: **the condition of the asset**, and **what happens if that condition worsens**. The same defect is routine work over a storage yard and a prioritised intervention over a hospital entrance.



CONDITION × CONSEQUENCE = PRIORITY

The same defect is routine work in one location and a prioritised intervention in another.

	Tier 3 Adaptable or short life	Tier 2 Standard	Tier 1 Critical
C4 Serious concern	Prioritise	Act now	Act now
C3 Significant deterioration	Plan	Prioritise	Prioritise
C2 Minor deterioration	Routine	Plan	Plan
C1 Performing as expected	Routine	Routine	Routine

Routine

Plan

Prioritise

Act now

Continue planned inspection; address at the next scheduled visit.

Schedule corrective action into normal maintenance work.

Obtain assessment and bring the intervention forward.

Control risk, consider restricting use, and obtain assessment before deciding anything else.

Condition on one axis, consequence on the other. The tiers are carried over from the ZIL Shades procurement guide so both documents use one language.

Used honestly, this does two things. It stops a cosmetic issue in a prominent location from consuming the budget that a real problem in a quiet corner needed. And it gives a facility manager something to show a finance director: a defensible reason why item nineteen was done before item four.

AN IMPORTANT LIMIT

The condition categories above are **conceptual categories to support decision-making. They are not validated safety classifications**, and they do not carry engineering meaning on their own.

Before a scale like this is used to make safety decisions on real assets, it should be developed into a proper methodology — with defined criteria, competency requirements and actions — appropriate to the asset type, by people qualified to develop it.



Decisions as the asset ages

Not every defect requires replacement, and not every ageing asset should automatically be repaired.

-
- 17** Repair: the problem or the cause?
 - 18** Refurbishment: extending useful life
 - 19** When replacement is the better decision
 - 20** Responsible lifecycle decisions

17 Repair: fixing the problem, or the cause?

Most repairs on outdoor structures are straightforward and successful. A tear is patched, a fitting is renewed, a coating is made good, and the asset carries on.

The repairs worth pausing over are the ones that come back.

A fabric that keeps tearing at the same corner is not suffering from bad luck; something at that corner is loading, chafing or restraining it in a way the design did not intend. A bolt that will not stay tight is telling you something is moving. A leak that has been sealed three times is a detailing problem being treated as a sealing problem. A coating that keeps failing at one spot is usually a place where water sits.

THE RULE OF THE THIRD REPAIR

The first repair is maintenance. The second may be coincidence. **The third repair in the same location is a diagnosis waiting to happen** — and it is almost always cheaper to find the cause than to keep buying the symptom.

There is also a category of repair that should not be attempted at all, because doing it removes evidence or makes the underlying condition worse. Painting over corrosion without knowing its extent hides it and traps it. Tightening a connection that keeps loosening removes the very signal that something is moving. Re-tensioning fabric that has gone slack without knowing why can transfer load into a structure that was not expecting it.

WHEN TO SEEK ASSESSMENT

Before repairing: the third repair in the same location · corrosion whose extent is unknown · any connection that has loosened more than once · slackness whose cause has not been established · damage to a structural element rather than to a covering.

18 Refurbishment: extending useful life

Between repairing a defect and replacing an asset sits an option that is frequently overlooked, and frequently the right answer.

Refurbishment is a planned intervention that renews significant parts of a structure while retaining what is still sound. On these assets it usually means replacing the membrane or fabric while keeping the frame; recoating steel that is structurally intact but whose protection has reached the end of its life; renewing cables, fittings and fixings; correcting drainage that never worked properly; or upgrading elements to suit a use that has changed.

	REPAIR	REFURBISHMENT	REPLACEMENT
Scope	One defect	Significant parts of the asset	The whole asset
Trigger	A finding	A planned decision based on condition	Continued intervention no longer makes sense
The frame	Untouched	Retained, and usually treated	Removed
Disruption	Low, short	Planned and contained	Highest
What it buys	Continued service	A meaningful extension of useful life	A new life, and a new set of decisions

Refurbishment tends to be appropriate when the primary structure is still suitable for the job, but the elements with shorter lives have reached the end of theirs – which is the ordinary condition of a well-built shade structure at some point in its life. The covering is often a planned renewal within the life of the frame, not a failure of it.

It also tends to be appropriate when repairs are becoming frequent enough to be inefficient, when appearance matters and has deteriorated, or when the asset needs to be brought up to a different standard for a changed use.

FOR FACILITY AND ASSET TEAMS

Refurbishment is a project, and deserves the same discipline as a new installation: a condition assessment first, a defined scope, confirmation that the retained structure suits the renewed elements, and **a new baseline record afterwards**. The asset that comes out of a refurbishment is not the asset that went in, and the records should say so.

It is also the point at which the original documentation earns its keep. Refurbishing a structure whose design basis and materials are unknown starts with an investigation that a handover file would have made unnecessary.

19 When replacement is the better decision

Refurbishment is not always right, and an attachment to keeping things going can be as expensive as a habit of replacing them early. There is a point at which continued intervention stops being good stewardship and becomes money spent deferring an inevitable decision.

Replacement deserves serious consideration when several of the following are true together.

- Deterioration is widespread rather than localised.
- The structural system is no longer appropriate for how the space is now used.
- Repairs are becoming more frequent, more expensive, or both.
- The cost of continued intervention is approaching the cost of a new asset.
- Materials or components can no longer be obtained, so repairs are improvised.
- Future maintenance would require disruption the operation cannot absorb.
- The asset no longer meets the operational requirement, whatever its condition.
- The risk profile has changed — the area below it is now used differently.

THE PRINCIPLE

The right time to replace an asset depends on condition, risk, future requirements and the value of continued intervention — not on the year it was installed.

Age is not a replacement criterion. It is a prompt to look properly.

One thing to carry into the replacement, from the procurement guide: before re-procuring, establish why the previous asset reached this point. Widespread corrosion at the bases of a structure standing in a wet corner is not solved by putting a new structure in the same wet corner. **Replacement without investigation buys the same failure again, in new materials, on the same timescale.**

20 Responsible lifecycle decisions

Every premature replacement consumes material, manufacturing, transport and disposal that a better decision might have avoided — and every one of those has a cost, environmental and commercial, that does not appear on the quotation.

But the answer is not to keep everything forever. Extending the life of an asset that is no longer suitable, or no longer safe, is not stewardship.

THE POSITION WORTH HOLDING

Maintain, repair and refurbish where it is responsible and appropriate. Replace or decommission when continued use is no longer justified.

Neither instinct — replace early, or keep forever — is a policy. The decision is made from condition, consequence and future use, and it is made again each time the asset is looked at properly.

In practice, the most environmentally significant thing most organisations can do with their outdoor assets is unglamorous: **inspect them, keep the drainage clear, and deal with small things while they are small.** An asset that reaches its intended life instead of half of it has avoided an entire replacement — which outweighs almost any material choice made at procurement.

And when replacement is genuinely right, it can be done consciously: understanding why the previous asset ended where it did, recovering what can be recovered, and specifying the next one so that it can be maintained, refurbished and eventually retired on purpose rather than in an emergency.



Running it as a system

A facility manager should not have to rediscover the history of a structure every time a new problem appears.

-
- 21** Documentation
 - 22** Building an outdoor asset register
 - 23** Lifecycle budgeting
 - 24** Common mistakes to avoid
 - 25** The lifecycle checklist

21 Documentation: preserving the memory of the asset

An asset with no history is harder and more expensive to manage than the same asset with a folder.

Picture the position of whoever holds your job in year seven. A canopy needs attention. Nobody knows what it is made of, what it was designed for, whether the slack corner has always been slack, what was repaired in year three, or who built it. Every option now begins with an investigation, and every judgement is made without a reference point.

THE PRINCIPLE

The purpose of documentation is not paperwork. It is preserving the memory of the asset. A facility manager should not have to rediscover the history of a structure every time a new problem appears.

What is worth keeping is modest: what the asset is and where; when it was installed and by whom; the drawings and material information; the warranty position; the baseline photographs; every inspection record; every repair and refurbishment, with dates; anything currently being monitored; and the contact details of whoever can work on it.

FOR FACILITY AND ASSET TEAMS

Two failure modes account for most lost asset records. The first is **storage in an individual's inbox** rather than in a system — records leave with the person. The second is **records that were never requested at handover**, which is a procurement failure rather than a maintenance one; tying a meaningful part of retention to the documentation package is the practical fix.

22 Building an outdoor asset register

For anyone responsible for more than two or three structures, the single highest-value step is not a maintenance contract. It is a list.

An asset register is simply a record of what you have, where it is, what condition it is in, and what is meant to happen next. It does not require a platform, a consultant or a budget line. A spreadsheet that is actually kept up to date outperforms a system nobody fills in.

FIELD	WHY IT EARNS ITS PLACE
Asset ID and location	You cannot discuss, schedule or budget for something that has no name.
Asset type and approximate size	Determines what inspection and maintenance it needs.
Installation date, where known	Useful context — never a substitute for condition.
Consequence tier	What sits beneath it. Drives inspection frequency and priority.
Current condition	The finding from the most recent inspection.
Date of last inspection, and next due	The two dates that make a regime real rather than theoretical.
Known issues and items being monitored	Stops findings from being rediscovered every year.
Previous interventions	Repairs and refurbishments, with dates. Reveals recurring problems.
Next planned action, and when	Turns a list of assets into a plan.
Where the documents are	A link or a folder reference. The most-skipped and most-missed field.

A register earns back the effort in four places: **budgeting**, because you can forecast rather than react; **inspection planning**, because you know what is due; **risk management**, because you can see which assets sit above the highest consequences; and **replacement forecasting**, because you can identify what is approaching the end of its life before it announces itself.

FOR FACILITY AND ASSET TEAMS

Start with what you have rather than waiting for completeness. A register listing every structure with a location, a tier and a photograph is immediately useful, and can be enriched as inspections happen. **A partial register maintained beats a complete one abandoned.**

23 Lifecycle budgeting

Maintenance appears in most budgets as an unwelcome surprise, which is odd, because almost none of it is surprising.

An outdoor structure has a predictable pattern of spending across its life. Knowing the shape of it does not make the money smaller, but it does move it from the emergency column into the planned one — and planned work is consistently cheaper and less disruptive than the same work done urgently.

COST CATEGORY	CHARACTER	WHERE IT IS USUALLY UNDERESTIMATED
Inspection	Small, regular, predictable.	Frequently omitted entirely, then paid for many times over.
Routine maintenance and cleaning	Small, regular. Drainage clearing belongs here.	Assumed to be inside somebody else's scope.
Minor repairs	Irregular, individually small.	Cheap when planned, expensive when urgent.
Monitoring	Very small.	Costs almost nothing and prevents larger spend.
Refurbishment	Occasional and significant.	Rarely budgeted in advance, though it is foreseeable.
Major component replacement	Occasional. Membrane renewal usually sits here.	Treated as a failure rather than as a planned renewal.
Emergency intervention	Unpredictable, and the most expensive per unit of work.	The category that grows when the others shrink.
Eventual replacement and removal	One-off, at end of life.	Almost never budgeted — and entirely certain.

Two honest cautions. **A lower installation cost is only one part of the cost of owning an asset** — but the reverse claim is not automatically true either. Higher initial spending does not guarantee lower lifecycle cost; it does so only where the additional spend buys durability, maintainability or reduced disruption that the asset's life and location actually require.

The reliable relationship is simpler: **spending that moves work from the emergency column to the planned column reduces both cost and disruption**, on almost every asset, in almost every location.

24 Common mistakes to avoid

THE MISTAKE	WHY IT COSTS MORE THAN IT SAVES
Assuming it is fine because it is still standing	Standing is a low bar. Deterioration is well advanced before it affects stability.
Patching the same place repeatedly	Each patch treats the symptom. The cause continues, and usually accelerates.
Letting untrained people adjust structural connections	Tightening or re-tensioning without understanding the system can transfer load somewhere it was not designed to go.
Changing membrane tension without understanding it	Prestress is a design condition, not a preference. Adjusting it changes forces throughout the structure.
Painting over corrosion	Hides the extent, traps moisture, and removes the evidence needed to assess it.
Letting drainage block	The cheapest maintenance task there is, and behind a large share of expensive problems.
Hanging equipment, signage or lighting without assessment	Adds load, and often adds wind load, to a structure designed without it.
Modifying a structure without reference to its design	Cutting, drilling or removing an element changes how load reaches the ground.
Waiting for an emergency to inspect an ageing asset	The most expensive inspection schedule available.
Replacing without understanding the previous failure	Buys the same problem again, in new materials.
Losing the drawings and records	Converts every future decision into an investigation.

None of these is a failure of care. Almost every one happens because nobody was ever given the responsibility, the information or the reason to do it differently – which is what this guide is for.

25 The lifecycle checklist

A working checklist for anyone responsible for outdoor structures. It applies to one villa canopy or four hundred car park bays.

Understanding what you have

- ☐ We know what outdoor assets we are responsible for.
- ☐ Each significant asset can be identified and located.
- ☐ We know, approximately, its age, type and size.
- ☐ We understand what sits beneath it and what would happen if it failed.

Baseline and records

- ☐ A baseline condition record exists, or has been created retrospectively.
- ☐ Photographs are taken from repeatable positions.
- ☐ Drawings, material information and warranties are held somewhere findable.
- ☐ Records are stored in a system, not in an individual's inbox.

Inspection

- ☐ An inspection approach exists, with intervals set from consequence, exposure, condition and access.
- ☐ The basis for those intervals is written down.
- ☐ Findings are recorded and compared with previous records.
- ☐ Known issues are tracked rather than rediscovered.
- ☐ Additional inspection follows storms, impacts and modifications.

Maintenance

- ☐ Routine maintenance and corrective repair are distinguished and budgeted separately.
- ☐ Drainage clearing is a scheduled task with a named owner.

- ☐ Recurring problems are investigated rather than repeated.
- ☐ Structural adjustment is carried out only by qualified people.

Monitoring

- ☐ Monitored conditions have a defined observation, method, frequency, reviewer and trigger.
- ☐ Monitoring is used for assessed conditions, not as a way of deferring assessment.

Lifecycle planning

- ☐ Priorities consider both condition and consequence.
- ☐ Refurbishment is considered before replacement is assumed.
- ☐ Replacement decisions are based on condition and use, not on age.
- ☐ Foreseeable renewals — membrane, coating — appear in the budget in advance.
- ☐ Major interventions are documented, and generate a new baseline.

Future responsibility

- ☐ The next person could pick this up and understand what they have inherited.
- ☐ We know why the last asset we replaced reached the end of its life.
- ☐ We have considered what these assets will leave behind when their purpose is complete.

IN CLOSING

The lifecycle mindset

The habit this guide is written against is not neglect. It is a way of seeing: the belief that an outdoor structure is either fine or broken, and that nothing needs deciding until it moves from the first state to the second.

Almost everything that matters happens in between. An asset is stable, or ageing normally, or showing something small, or worth watching, or worth repairing, or ready for renewal, or past the point where renewal makes sense. Managing it well means knowing which of those is true today, and choosing the appropriate next step — again and again, for as long as it stands.

THE THREE SENTENCES BEHIND THIS GUIDE

You cannot manage what you do not understand.

You cannot understand what you do not observe.

And you should not wait for failure before deciding what to do next.

Inspect what exists. Understand its condition. Maintain what should be maintained. Monitor what needs observing. Repair what can responsibly be repaired. Refurbish where useful life can be extended. Replace when continued intervention no longer makes sense. And manage every stage understanding what is being kept, what is being spent, and what will eventually be left behind.

ABOUT THIS GUIDE

ZIL Shades designs, engineers and installs awnings, car parking shades, tensile shades and tents — and then inspects, maintains, repairs, refurbishes and eventually decommissions them. This guide describes how that thinking works, whoever ends up doing it for you.

It completes a set of four: Before You Buy Shade, Before You Issue the RFQ, Before You Approve the Material, and this one.

Performance Beyond Installation.

SCOPE OF USE

This guide provides general educational information to support asset management and decision-making. It states no inspection frequencies, maintenance intervals, material lifespans, structural limits, failure thresholds, engineering standards, safety classifications or replacement criteria. The condition categories described are conceptual aids to prioritisation and are not validated safety classifications. Inspection findings, maintenance requirements, structural safety, repair methods and replacement decisions should be evaluated by appropriately qualified professionals on the basis of the specific asset, its condition, environment and intended use.

ZIL SHADES

MADE FOR LIFE UNDER THE SUN



You cannot manage what you do not understand.
You cannot understand what you do not observe.
And you should not wait for failure
before deciding what to do next.

Performance Beyond Installation.

ZIL Shades is a brand of SHADES HOUSE TENTS & SHEDS TR L.L.C.S.P,
licensed in the United Arab Emirates.

zilshades.com